



## HT-9819 CFM/CMM Thermo-Anemometer

CFM/CMM Thermo- Anemometer measures remote surface temperatures

Max/Min/Avg value with relative time stamp

Low battery indication and Auto Power Off

Display Air Flow (CFM/CMM), or Air Velocity plus

Temperature simultaneously

### Features

Simultaneous display of Air Flow or Air Velocity

plus Ambient Temperature

Easy to set Area dimensions (cm<sup>2</sup>) are stored in the meter's internal memory for the next power on

Resolution of 0.01m/sec

20 point average for Air Flow

Super large LCD Backlit Display

High Sensitive and Accurate

Meter Size(HxWxD):202mmx85mmx48mm

Weight:450g

Accessories: 9V battery ,black bag,manual , color box and Anemo probe

### Specifications

Air Velocity	Range	Accuracy
m/s (meter per second)	0.40~45.00	±3%±0.20m/s
ft/min(feet per minute)	80~8858	±3%±40ft/min
km/h(kilometers per hour)	1.4~162.0	±3%±0.8km/h
MPH(miles per hour)	0.9~100.4	±3%±0.4MPH
Knots(nautical miles per hour)	0.8~87.0	±3%±0.4knots
Air Temperature	14-140°F(-10-60°C)	±4.0°F(2.0°C)
Air Flow	Range	Area
CFM	0-999900	0-999.9ft <sup>2</sup>
CMM	0-999900	0-999.9m <sup>2</sup>

