

## Low Speed Centrifuge

Low speed clinical centrifuges are widely used in the medical industry. Ideal for separation of serum, plasma, urine, fecal samples in biochemical & medical laboratories. It is an essential equipment of every clinical laboratory, blood bank, medical college and medical research institute.

### INNO-LSC-4C feature:

- ◆ Max. capacity 50ml×4, Adapt to different sizes of blood collection tubes and centrifuge tubes suitable for swing out rotor and angle rotor.
  - ◆ Rotor speed can be set in RPM/RCF, with 3 programs storage capacity for routine applications.
  - ◆ Max. speed 4000rpm.
  - ◆ Automatic internal diagnosis and self-detection.
- Maintenance-free brushless DC motor



### Available Rotors:

<p><b>S6-15</b> Max. speed: 4000rpm Rotor capacity: 15ml×6 Rotor material: Aluminum alloy</p>	<p><b>S4-50</b> Max. Speed: 4000rpm Rotor capacity: 50ml×4 Rotor material: Aluminum alloy</p>
<p><b>A8-15P</b> Max. Speed: 4000rpm Rotor capacity: 15ml×8 Rotor material: High strength plastic</p>	<p><b>A12-10P</b> Rotor capacity: 15ml×8, 10ml×12 Rotor material: High strength plastic</p>

### Technical Specifications:

Model	INNO-LSC-4C
Speed range	500-4000rpm increment: 100rpm
Max. RCF	2500×g
Speed accuracy	±100rpm
Rotor	Swing6×15ml
	Swing4×50ml
	Angle 24×15 ml, Angle 12×10ml/8×15ml
Run time	1-99min, HOLD
Motor	Brushless DC motor
Display	LCD
Program	Blood: 3200rpm, 10min.
	Urine: 1800rpm, 5min.
	Faecal: 1300rpm, 10min.
Safety Device	Automatic internal diagnosis
Acceleration/deceleration	3↑4↓steps
Power	Single phase,
	100V-240V, 50Hz/60Hz
Dimension(W×D×H)	364×440×268mm
Weight	14.5kg
Noise	≤62dB(A)

### Available Adaptor:

	<p>50 ml adaptor for 17 x 120mm, 13/16 x 100mm tube 4 pcs/pack for S4-50</p>
	<p>15ml adaptor for 17×120mm, 13/16×100mm tube 24 pcs/pack, for S6-15, A24-15P, A8-15P</p>
	<p>5ml adaptor for 13×75mm blood collection tube 24 pcs/pack for S4-50, S6-15, A24-15P</p>